

**WEST COAST FACTORY
COLORS AVAILABLE**

SELECT DESIRED COLOR:

- ALMOND
- LINEN GRAY

SELECT DESIRED SIZE:

- 8x8x1-5/8" (200x200x40mm)
- 12x24x1-5/8" (300x600x40mm)
- 16"x16"x1-5/8" (400x400x40mm)


SELECT DESIRED FINISH:

- POLISHED
- POLISHED & ANTIQUED


PACKING:

NOMINAL SIZE (in)	SQ.FT.PER PALLET	WEIGHT PER PALLET
8x8x1-5/8"	160	2870
12x24x1-5/8"	156	2808
16x16x1-5/8"	160	2870


TOP VIEW



TOP VIEW



SIDE VIEW



SIDE VIEW

NOTES:

- PAVERS ARE CALIBRATED TO ACHIEVE A UNIFORM THICKNESS OF APPROXIMATELY 1 5/8". DIMENSIONAL TOLERANCE $\pm 1/16"$.
- BECAUSE OF COLOR DYE AND NATURAL RAW MATERIALS INCONSISTENCIES, PRODUCTS WILL HAVE COLOR SHADE AND TEXTURE VARIATIONS.
- DUE TO THE PROCESS REQUIRED TO MANUFACTURE, PACKAGE, DELIVER, UNPACK, INSTALL AND COMPACT, SMALL CHIPPING CAN BE EXPECTED.
- IN SHELLLOCK® PAVERS, NATURAL SHELLS ARE EMBEDDED AT DIFFERENT DISTANCES FROM THE SURFACE OF THE MATERIAL, AND THEN POLISHED. THEREFORE, A SMALL PERCENTAGE OF THE SHELLS ARE EXPECTED TO COME LOOSE FROM THE SURFACE AND EDGES OF THE TILE. THIS OCCURRENCE WILL DIMINISH OVER A SHORT SPAN OF TIME AND IN NO WAY WILL AFFECT THE STRENGTH OF THE PRODUCT.
- INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH ICPI TECH SPECS 10.
- THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.



LIMESTONELOCK® PEDESTRIAN PAVERS

SAND-SET INTERLOCKING PAVERS AND PAVING SLABS

REV. DATE:

01/16/2020

artisticpavers.com

MAIN OFFICE- EAST COAST: (305) 653-7283

WEST COAST OFFICE: (520) 426-3479